



LAMINATOR MOD. STONE 1600

CHARACTERISTICS

CODE 100006

“Stone 1600” is a highly professional laminator with refined details and elegant design.

It is robustly designed with high-quality materials. The paper insertion surface is made of aluminium; the large diameter silicone roller has a span of 1700 mm, so it can laminate 1650 mm and calender 1700 mm.

“Stone 1600” is equipped with 130 mm rollers.

The upper roller can reach a maximum temperature of 120°C, which allows hot and cold laminating of the film.

Equipped with a Roll-to-Roll rewinding roller, which can reach a maximum speed of 12 m/minute.

During use, it provides safety to the operator, who, thanks to the new self-locking roller shafts (which are even lighter), allows film changeovers to be made quickly and easily with maximum safety, precisely because there is an optical barrier in front of the rollers on all the machines.

+ TECHNICAL SPECIFICATIONS

Maximum rolling width: 1630 mm/64.

Roller diameter: 130 mm.

Single-sided lamination mode.

Nominal power: 220V.

Max thickness: 25 mm.

Infrared heating.

Nominal input voltage: 220V.

Speed: 12m/min.

Preheating time: 10-15 min.

Temperature: 120° C.

Power: 0,8kW/h.

Size: 660x2250x1450 mm.

Packaging dimensions: 850x2200x7600 mm.

Weight of the laminator: 180 kg.



FOR MORE INFO
VISIT **MARGRAFITALY.IT**